



SmartMailer

Automated padded and rigid envelope packaging

KEY FEATURES

- Works with multiple envelope types to insert variable products up to 1" (25.4mm) thickness
- Rotary feeders and shuttle feeders available for standard size products, or manual feed modules for variable items
- Real-time tracking and selective feeding made possible through barcode matching
- In-line printing produces personalized mail pieces and labels
- In-line color invoice printing and folding

Evolve your E-commerce and fulfillment operations from the labor-intensive process of manually packing merchandise mailers with the SmartMailer package inserter from Bell and Howell. Accurately and automatically process as many as 2,500 merchandise packages per hour.

The SmartMailer is a compact, continuous motion inserter with flexibility to work with rigid mailers or padded envelopes. These packages can be automatically printed in-line, tracked and sorted to simplify the outgoing shipments.

ADAPTABLE INSERTING

Free your business from manual inserting with packaging automation for rigid or bubble mailers. SmartMailer is a compact continuous motion inserter which runs a wide range of products. Thanks to its modular configuration, SmartMailer can be customized to insert a variety of products through use of rotary feeders, shuttle feeders and manual feeding areas for non-standard contents.

To eliminate packaging and labeling errors, the SmartMailer delivers high-integrity data during the packing process with real-time product tracking controls, barcode matching through optical readers or cameras, and a final daily report of all production runs.

Additional customization options are available for in-line printing and selective feeding informed by database entries which correspond to the mailpiece barcode. All adjustments are simple, ensuring quick and correct set up.

PC ADD CONTROLLER

Operator User Interface available in multiple languages for:

- Document handling
- Barcode readers (matching, tracking, sequence control, no read, lot control)
- Addressing
- Sorting
- Read & Print

Data Integrity

- Reports
- Logs
- Database update

Management of File-based production

- Selectivity
- Printing of invoices and delivery notes
- Printing and dispatch labels for the carrier
- Connects to WMS system

Management of packaging line devices

- Feeders
- Rejects
- Ink-jet printers
- Labelers
- Weighing systems

COMMON SPECS	
Padded Mailers Standard envelope size #1	Width: 11.42" (290 mm) Length: 9.45" (240 mm) Flap: 1.38" (35 mm)
Padded Mailers Standard envelope size #2	Width: 11.42" (290 mm) Length: 14.96" (380 mm) Flap: 1.57" (40 mm)
Rigid Mailers Standard envelope size #1	Width: 13.19" (335 mm) Length: 9.25" (235 mm) Flap: 1.97" (50 mm)
Rigid Mailers Standard envelope size #2	Width: 15" (381 mm) Length: 9.45" (240 mm) Flap: 1.77" (45 mm)
Min. Enveloping Thickness	.08" (2 mm)
Max. Enveloping Thickness	1" (25.4 mm) not compressed
Max Speed	2,500 packages/hour

FOR MORE INFORMATION VISIT: BELLHOWELL.NET



bellhowell.net

800-220-3030

3791 South Alston Ave,
Durham, NC 27713

© 2017 Bell and Howell, LLC. All rights reserved. Bell and Howell and the Bell and Howell logo are trademarks or registered trademarks of Bell and Howell, LLC. All other marks are the property of their respective owners. Specifications are subject to change without notice. Actual performance results may vary.

BH_PARC_DSHT_1008_08_JUN_2018